

## Strain gauge, hand-held measuring instrument



### Description

The E3906 is an economical handheld measuring instrument. The freely scalable LCD-display has 4½ digits and can be used for strain gauge signals with 0,35 – 3,5 mV/V.

The compact handheld measuring instrument is highly flexible in application.

Commercial external accessible batteries or accu as well as a plug power pack with integrated accu charging function can be used alternatively.

The power saving mode with timer function switches off the instrument automatically after 15 min.

An integrated maximum value memory and a signal inverse function can be turned on and off at any time by a key switch. The status is indicated by LED's on the keys.

Another key switch turns on the 100% calibration control made of the sensor, thus the E3906 can simply be in-calibrated to a sensor and the calibration can be checked at any time.

### Features

- Display and decimal digit freely scalable
- Mains-, battery-, accu operation
- Disconnection after 15 min
- Calibration control switch
- Maximum value memory
- Signal conversion switch
- Integrated accu charger
- 4½ digit LCD-display
- Simplest calibration
- SUB-D15-connector for loadcell

### Applications

- Measurements and control instruments
- Instrument manufacturing
- Machine equipment
- Building of fixtures and special machinery manufacturing
- Calibration service

**Model: E3906**

## Technical data

Model	E3906
Output	
- Display	4½ digit LCD-display
- Accuracy	0.2% of F.S. ± 3 digits
Input	
- Signal	0...14 mV
- Sensor supply	4 VDC, max. 15 mA
- Limit frequency	4 Hz (3 dB);
Setting	Through DIP-switches and potentiometer
Power requirement/operating time	with batteries, 4xMicro 750 mAh: > 40h with batteries: > 50 h
Nominal temperature range	+15°C ... +35°C
Service temperature range	+5°C ... +45°C
Storage temperature range	-10°C ... +70°C
Protection type (acc. to EN 60 529/IEC 529)	IP 40
Electrical connection	Force transducer: SUB-D15-socket
Housing	
- Material	Plastic
- Dimensions	80 x 125 x 40 mm
Weight	250 g
Rise time maximum value memory	250 ms -3 dB
Reading rate	2.5 s
Indication extent	0 - ±19999
Bridge resistance of SG*	350 ...2000 Ω
Input sensitivity	0.35 ...3.5 mV/V
<b>Accessories</b>	
Accumulators	
Battery charger	

\* ) SG = strain gauge