

Differential pressure gauge Model A2G-10

WIKA data sheet PM 07.40



Applications

- For dry, clean, non-aggressive gases, usually air
- Fan and blower monitoring
- Differential pressure monitoring in filters
- Overpressure monitoring in cleanrooms
- For very low pressures

Special features

- Zero adjustment in front
- Red mark pointer
- Simple mounting and dismounting
- Two-part construction (measuring element and case)
- Optional version with additional electrical output signal (model A2G-15)



Differential pressure gauge model A2G-10

Description

Design

Per EN 837-3 and ventilation and air-conditioning (VAC) regulations

Nominal size in mm

110

Accuracy class

3.0

Scale ranges

0 ... 50 Pa to 0 ... 12500 Pa
-25 ... +25 Pa to -1500 ... +1500 Pa
further plus/minus ranges on request

Pressure limitation

Steady: full scale value
Fluctuating: full scale value

Overpressure safety

20 kPa

Max. working pressure (static pressure)

20 kPa

Permissible temperature

Ambient: -30 ... +80 °C
Medium: -16 ... +50 °C

Temperature effect

When the temperature of the measuring system deviates from the reference temperature (+20 °C):
max. $\pm 0.5 \%$ / 10 K of full scale value

Ingress protection

IP 54 per EN 60529 / IEC 529

Standard version

Process connection

Plastic,
lower mount (LM) or back mount
G 1/8 (female, in case) for hose connector
Hose connection inner diameter 4 or 6 mm

Standard accessories

- 3 mounting screws
- Straight or angled threaded pressure connection G 1/8 for inner diameter 4 or 6 mm

Separating diaphragm

Silicone

Movement

Contact-free transmission

Dial

Aluminium, scale angle 90°

Pointer and mark pointer

Plastic

Case

Plastic,
Basic case, case for panel/wall mounting and ring

Window



Makrolon

Options

- Ingress protection IP 65
- Internationally recognised traceable calibration certificate
- Measuring hose PVC or silicone, inner diameter 4 or 6 mm, length 25 m
- 2 duct connectors
- Output signal 4 ... 20 mA, 2-wire, power supply DC 14 V or output signal 0 ... 10 V, 3-wire, power supply DC 15 V (see data sheet PV 17.40)
- Without case

Dimensions in mm

Standard version



Ordering information

Model / Connection location / Wall mounting or panel mounting / Inner diameter of the threaded pressure connection / Scale range / Options

© 2008 WIKA Alexander Wiegand SE & Co. KG, all rights reserved.
The specifications given in this document represent the state of engineering at the time of publishing.
We reserve the right to make modifications to the specifications and materials.



WIKAL
WIKAL Alexander Wiegand SE & Co. KG
Alexander-Wiegand-Straße 30
63911 Klingenberg/Germany
Tel. (+49) 9372/132-0
Fax (+49) 9372/132-406
E-mail info@wika.de
www.wika.de